



## References

- YBCO: Tape, || Tape-plane, SuperPower. REBCO: SP26 tape, 50  $\mu\text{m}$  substrate, 7.5%Zr. Measured at NHMFL by Valeria Braccini, Jan Jaroszynski and Aixia Xu: <http://dx.doi.org/10.1088/0953-2048/24/3/035001>
- YBCO: Tape,  $\perp$  Tape-plane. REBCO: SP26 tape, 50  $\mu\text{m}$  substrate, 7.5%Zr. Measured at NHMFL by Valeria Braccini, Jan Jaroszynski and Aixia Xu: <http://dx.doi.org/10.1088/0953-2048/24/3/035001>
- Bi-2223: B || Tape plane: Sumitomo Electric Industries. Measured at NHMFL (D. Abraimov) unpublished
- Bi-2223 (Carrier Controlled): B  $\perp$  Tape-plane "DI" BSCCO "Carrier Controlled" Sumitomo Electric Industries (MEM'13 presented by Kazuhiko Hayashi).
- Bi-2223 (2012 production): B  $\perp$  Tape-plane "DI" BSCCO (measured at NHMFL by Jianyi Jiang and Dmytro 2212: OST NHMFL 50 bar overpressure HT. Sample pmm170123, 0.78 mm Diam. (after HT) , OST 55x18 composite
- Nb-47Ti: 0-6 T - Boutboul et al. MT-19: Boutboul, T.; Le Naour, S.; Leroy, D.; Oberli, L.; Previtali, V.; , "Critical Current Density in Superconducting Nb-Ti Strands in the 100 mT to 11 T Applied Field Range," Applied Superconductivity, IEEE Transactions on , vol.16, no.2, pp.1184-1187, June 2006.
- [doi: 10.1109/TASC.2006.870777](https://doi.org/10.1109/TASC.2006.870777)
- Nb-47Ti 1.8 K 5-8 T Maximal for whole LHC NbTi strand production (CERN-T. Boutboul '07)
- Nb-47Ti 4.2 K for the LHC insertion quadrupole strand (T. Boutboul, S. Le Naour, D. Leroy, L. Oberli, and V. Previtali, "Critical Current Density in Superconducting Strands in the 100 mT to 11 T Applied Field Range," IEEE Transactions on Applied Superconductivity, vol. 16, no. 2, pp. 1184–1187, Jun. 2006
- Nb-47Ti 4.22 K for 11.75 T Iseult/INUMAC MRI: Kanithi H, Blasiak D, Lajewski J, Berriaud C, Vedrine P and Gilgrass G 2014 Production Results of 11.75 Tesla Iseult/INUMAC MRI Conductor at Luvata IEEE Transactions on Applied Superconductivity 24 1–4 <http://dx.doi.org/10.1109/TASC.2013.2281417>
- Nb<sub>3</sub>Sn (RRP®): Non-Cu J<sub>c</sub> Internal Sn OI-ST RRP® 1.3 mm, Parrell, J.A.; Youzhu Zhang; Field, M.B.; Cisek, P.; Seung Hong; , "High field Nb<sub>3</sub>Sn conductor development at Oxford Superconducting Technology," Applied Superconductivity, IEEE Transactions on , vol.13, no.2, pp. 3470- 3473, June 2003.
- Applications J. A. Parrell, M. B. Field, Y. Zhang, and S. Hong, AIP Conf. Proc. 711, 369 (2004), DOI:10.1063/1.1774590.
- Nb<sub>3</sub>Sn (High Sn Bronze): T. Miyazaki et al. MT18 - fig3, Miyazaki, T.; Kato, H.; Hase, T.; Hamada, M.; Murakami, Y.; Itoh, K.; Kiyoshi, T.; Wada, H.; , "Development of high Sn content bronze processed Nb<sub>3</sub>Sn superconducting wire for high field magnets," Applied Superconductivity, IEEE Transactions on , vol.14, no.2, pp. 975- 978, June 2004
- [doi: 10.1109/TASC.2004.830344](https://doi.org/10.1109/TASC.2004.830344)
- MgB<sub>2</sub>: 18 Filament - The OSU/HTRI C 2 mol% AIMI ("Advanced Internal Mg Infiltration") 33.8 Filament to strand ratio, 39.1% MgB<sub>2</sub> in filament. (<http://dx.doi.org/10.1088/0953-2048/25/11/115023>)
- G. Z. Li, M. D. Sumption, J. B. Zwyer, M. A. Susner, M. A. Rindfleisch, C. J. Thong, M. J. Tomsic, and E. W. Collings, "Effects of carbon concentration and filament number on advanced internal Mg infiltration-processed MgB<sub>2</sub> strands," Superconductor Science and Technology, vol. 26, no. 9, p. 095007, Sep. 2013.

[Links to ASC, MT and ICMC Proceedings can be found on the conferences page.](#)